


VARDAflex EX Outdoor LD EX-Outdoor LED-Flex. 6500K

Article nr.: S71904

flexible LED strip EX protected and sealed in UV, solvent and salt water · resistant white silicone · for indoor and outdoor use, IP67 · cuttable every 83.33 mm or 7 LEDs · amount of LEDs per meter: 84 · LED pitch: 11.90 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1000 lm · power per meter: 12 W · lifespan L70: >= 50.000 h · WxH in mm: 20 x 10 · ambient working temperature: -30 bis +40°C · ambient installation temperature: +10 bis +40°C · maximum length per connection: 20 meter · bending radius vertical: 75 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094719047
Housing colour	Weiss
Width	20.00 mm
Height	10.00 mm
LED colour	ca. 6500K kaltweiß
Lamp	including LED
IP rating	67
Voltage	24 V
Material	Kunststoff



VARDAflex EX Outdoor LD EX-Outdoor LED-Flex. 6500K

Article nr.: S71904

TECHNICAL DATA

Temperature range	-30 - 40
LED per meter	84
Dimension of segments	8.33 mm
CRI	≥ 80
Suitable light source	



VARDAflex EX Outdoor LD EX-Outdoor LED-Flex. 6500K

Article nr.: S71904

TECHNICAL DRAWING

