rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin Tube DTW 1800-3000K LD S?-?? Flex.LEDStrip, 24V, DTW

Article nr.: S76019

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solventresistant white silicone · for indoor- and outdoor use, IP68 · · Cuttable every 83,33 mm / 12 LEDs · Amount of LEDs per meter: 144 · LED pitch: 6,94 mm · Beam angle: 160° · CRI: >80 · Light colour: 1800 - 3000 K DimToWarm · Luminous flux per meter: 560 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · WxH in mm: 11.5 x 29 · · Temperature range: -40 to +55°C · Processing temperature: +10 to +55°C · Maximum length per connection: 15 meter · Bending radius: 60 mm horizontal

TECHNICAL DATA

Unit Code	metre
BAR code	4012094760193
Housing colour	Weiss
Width	11.50 mm
Height	29.00 mm
LED colour	3000-1800K Dim to Warm
Lightoutput per LED	3.89 lm
Lamp	including LED
IP rating	68
Voltage	24 V

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin Tube DTW 1800-3000K LD S?-?? Flex.LEDStrip, 24V, DTW

Article nr.: S76019

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 55
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	