rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin SV - 2700K LD S?-??
Flex.LEDStrip, 24V, UWW

Article nr.: S76033

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP68 · · Cuttable every 83.33 mm / 6 LEDs · Amount of LEDs per meter: 72 · LED pitch: 13.89 mm · Beam angle: 120° · CRI: >80 · Luminous flux per meter: 360 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · WxH in mm: 11.5 x 21 · · Temperature range: -40 to +55° C · Processing temperature: +10 to +55° C · Maximum length per connection: 15 metre · Bending radius horizontal: 60 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094060330
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per LED	5.00 lm
Lamp	including LED
IP rating	68
Voltage	24 V

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin SV - 2700K LD S?-??
Flex.LEDStrip, 24V, UWW

Article nr.: S76033

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 55
LED per meter	72
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin SV - 2700K LD S?-??
Flex.LEDStrip, 24V, UWW

Article nr.: S76033

TECHNICAL DRAWING

