




VARDAflex Platin TVQ DTW 1800-3000K LD S?-?? Flex.LEDStrip, 24V, DTW

Article nr.: S76069

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP68 · cuttable every 83.33 mm / 12 LEDs · amount of LEDs per meter: 144 · LED pitch: 6.94 mm · beam angle: 120° · CRI: >80 · light colour: 3000-1800 K Dim To Warm · luminous flux per meter: 600 lm · voltage: 24V DC · power per meter: 12 W · lifespan L70B50: >= 36,000 h · WxH in mm: 16 x 17 · Temperature range: -40 to +55°C · Processing temperature: +10 to +55°C · Maximum length per connection: 15 meter · min. bending radius vertical: 150 mm · This product contains a light source of energy efficiency class G.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094060699
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	3000-1800K Dim to Warm
Lightoutput per LED	4.17 lm
Lamp	including LED
IP rating	68
Pno	0,00 W






VARDAflex Platin TVQ DTW 1800-3000K LD S?-?? Flex.LEDStrip, 24V, DTW
Article nr.: S76069

TECHNICAL DATA

Voltage	24 V
Material	Kunststoff
Temperature range	-40 - 55
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin TVQ DTW 1800-3000K LD S?-?? Flex.LEDStrip, 24V, DTW
Article nr.: S76069

TECHNICAL DRAWING

