




VARDAflex Platin TVQ RGBW-27K Int.12 LD S?-?? Flex.LEDStrip, 24V, RGBW

Article nr.: S76078

Flexible LED Stripe sealed in UV-, Chlorine-, · salt water- and solvent resitant white silicone · for indoor- and outdoor use, IP68 · · cuttable every 83.33 mm / 7 LEDs · amount of LEDs per meter: 84 · programmable pixel per meter: 8 · LED pitch: 11.90 mm · beam angle: 120° · CRI: >80 · light colour: RGBW (2700 K) · luminous flux per metre: 200 lm · power per meter: 22 W · lifespan L70: >= 36.000 h · WxH in mm: 16 x 17 · · temperature range: -40 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 8 meter · bending radius vertical: 150 mm · Attention: do not run all at same time on · maximum load (max. 80%)

TECHNICAL DATA

Unit Code	metre
BAR code	4012094060781
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
Lamp	including LED
IP rating	68
Voltage	24 V
Material	Kunststoff
Temperature range	-40 - 45






VARDAflex Platin TVQ RGBW-27K Int.12
LD S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76078

TECHNICAL DATA

LED per meter	84
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin TVQ RGBW-27K Int.12
LD S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76078

TECHNICAL DRAWING

