




VARDAflex Platin TVQ RGBW-27K Int.6 LD S?-?? Flex.LEDStrip, 24V, RGBW

Article nr.: S76081

Flexible LED strip encapsulated in UV-, chlorine-, salt water- and solvent resistant white silicone · for indoor and outdoor use, IP68 · every 166.67 mm / 14 LEDs cuttable · number of LEDs per metre: 84 · LED pitch: 11.90 mm · beam angle: 120° · CRI: >80 · luminous flux per metre: 310 lm · power per metre: 22 W · lifespan L70B50: >= 36,000 h · WxH in mm: 16 x 17 · temperature range: -40 to +45 °C · installation temperature: +10 to +45 °C · maximum length per connection: 8 metres for static colours, 12 metres for running light · bending radius vertical: 150 mm · Attention: do not operate all colours simultaneously · at the same time under full load (max. 80%)

TECHNICAL DATA

Unit Code	metre
BAR code	4012094060811
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	RGBW 2700K
Lightoutput per LED	3.69 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Platin TVQ RGBW-27K Int.6
LD S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76081

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 45
LED per meter	84
Dimension of segments	166.67 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin TVQ RGBW-27K Int.6
LD S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76081

TECHNICAL DRAWING

