



VARDAflex Platin SV RGBW-3000K LD
S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76135

Flexible LED Stripe sealed in UV-, Chlorine-, · salt water- and solvent resitant white silicone · for indoor- and outdoor use, IP68 · · cuttable every 100 mm / 6 LEDs · Amount of LEDs per meter: 60 · LED spacing: 16,67 mm · Beam Angle: 120° · CRI: 80 · Light flux per meter: 315 lm · Load per Meter: 15 W · Lifespan L70: >= 36,000 h · WxH in mm: 11.5 x 21 · · Temperature range: -40 to +50°C · Processing temperature: +10 to +50°C · Maximum length per connection: 8 meter · Bending radius: 60 mm · Attention: do not run all at same time on · maximum load (max. 80%)

TECHNICAL DATA

Unit Code	metre
BAR code	4012094061351
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	RGBW 3000K
Lightoutput per LED	5.25 lm
Lamp	including LED
Voltage	24 V
Material	Kunststoff



VARDAflex Platin SV RGBW-3000K LD
S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76135

TECHNICAL DATA

Temperature range	-40 - 50
LED per meter	60
Dimension of segments	100.00 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	



VARDAflex Platin SV RGBW-3000K LD
S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76135

TECHNICAL DRAWING

