



VARDAflex Platin SV RGBW-2700K LD


S?-?? Flex.LEDStrip, 24V, RGBW

Article nr.: S76136

Flexible LED Stripe sealed in UV-, Chlorine-, · salt water- and solvent resitant white silicone · for indoor- and outdoor use, IP68 · · cuttable every 100 mm / 6 LEDs · Amount of LEDs per meter: 60 · LED spacing: 16,67 mm · Beam Angle: 120° · CRI: 80 · Light flux per meter: 315 lm · Load per Meter: 15 W · Lifespan L70: >= 36,000 h · WxH in mm: 11.5 x 21 · · Temperature range: -40 to +50°C · Processing temperature: +10 to +50°C · Maximum length per connection: 8 meter · Bending radius: 60 mm · Attention: do not run all at same time on · maximum load (max. 80%)

TECHNICAL DATA

Unit Code	metre
BAR code	4012094061368
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	RGBW 2700K
Lightoutput per LED	5.25 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Platin SV RGBW-2700K LD
S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76136

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 50
LED per meter	60
Dimension of segments	100.00 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin SV RGBW-2700K LD
S?-?? Flex.LEDStrip, 24V, RGBW
Article nr.: S76136

TECHNICAL DRAWING

