




VARDAflex Platin Select SVQ - 2000-3200K LD S?-?? Flex.LEDStrip, 24V, Select

Article nr.: S76189

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP68 · cuttable every 83.33 mm / 12 LEDs · number of LEDs per meter: 144 · LED pitch: 6.94 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 594 lm · voltage: 24V DC · power per meter: 12 W · lifespan L70B50: >= 36.000 h · WxH in mm: 16 x 17 · Temperature range: -40 to +55°C · Processing temperature: +10 to +55°C · Maximum length per connection: 15 meter · min. bending radius vertical: 150 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094761893
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	3200-2000K tunable white
Lightoutput per LED	4.13 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Platin Select SVQ - 2000-3200K LD S?-?? Flex.LEDStrip, 24V, Select

Article nr.: S76189

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 55
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin Select SVQ - 2000-3200K LD S?-?? Flex.LEDStrip, 24V, Select

Article nr.: S76189

TECHNICAL DRAWING

