




VARDAflex Platin GIGA TVQ DMX-SIX LD S?-?? Flex.LEDStrip, 24V, 2700K

Article nr.: S76213

Flexible LED stripe sealed in UV-, chlorine-, · salt water- and solvent resistant white silicone · for indoor and outdoor use, IP68 · each individual segment separately programmable · and individually controllable · cuttable every 166.67 mm / 14 LEDs · amount of LEDs per meter: 84 · IC type: UCS512CN · LED pitch: 11.9 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 844 lm · power per meter: 15 W · lifespan L70B50: >= 36,000 h · WxH in mm: 22 x 19 · · ambient working temperature: -40 bis +50°C · ambient installation temperature: +10 to +50°C · maximum length per connection: 8 meter at static colours · maximum length per connection: 12 meter at dynamic running light effect · bending radius vertical: 200 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094062136
Housing colour	Weiss
Width	22.00 mm
Height	19.00 mm
LED colour	ca. 2700K ultra warmweiß
Lamp	including LED
IP rating	68
Voltage	24 V
Material	Kunststoff






VARDAflex Platin GIGA TVQ DMX-SIX LD
S?-?? Flex.LEDStrip, 24V, 2700K
Article nr.: S76213

TECHNICAL DATA

Temperature range	-40 - 50
LED per meter	84
Dimension of segments	166.67 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin GIGA TVQ DMX-SIX LD
S?-?? Flex.LEDStrip, 24V, 2700K
Article nr.: S76213

TECHNICAL DRAWING

