rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin GIGA TVQ RGBW+WW LD S?-?? Flex.LEDStrip, 24V, RGBW(5700K)+WW(2200K)

Article nr.: S76239

flexible LED Stripe sealed in UV-, chlorine-, · salt water- and solvent resistant white silicone · for indoor and outdoor use, IP68 · cuttable every 83.33 mm / 21 LEDs · number of LEDs per meter: 252 · LED pitch: 7.93 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1000 lm · luminous flux per meter 2200 K: 285 lm · luminous flux per meter 5700 K: 310 lm · power per meter: 16 W · lifespan L70B50: >= 36,000 h · WxH in mm: 22 x 19 · temperature range: -40 to +55°C · processing temperature: +10 to +55°C · maximum length per connection: 7 meter · bending diameter: 300 mm · attention: do not run all colors at same time on · maximum load (max. 80%) · This product contains a light source of energy efficiency class D

TECHNICAL DATA

Unit Code	metre
BAR code	4012094062396
Housing colour	Weiss
Width	22.00 mm
Height	19.00 mm
LED colour	RGBWWW 5700+2200K
Lightoutput per LED	3.97 lm
Lamp	including LED
IP rating	68
Voltage	24 V

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin GIGA TVQ RGBW+WW LD S?-?? Flex.LEDStrip, 24V, RGBW(5700K)+WW(2200K)

Article nr.: S76239

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 55
LED per meter	252
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	



rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Platin GIGA TVQ RGBW+WW

LD S?-?? Flex.LEDStrip, 24V, RGBW(5700K)+WW(2200K)

Article nr.: S76239

TECHNICAL DRAWING

