




VARDAflex Platin Ultra SVQ - 2700K LD S?-?? Flex.LEDStrip, 24V, UWW

Article nr.: S76583

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP68 · Cuttable every 55.56 cm / 6 LEDs · Amount of LEDs per meter: 108 · LED pitch: 9.26 mm · Beam angle: 120° · CRI: >80 · Luminous flux per meter: 660 lm · Voltage: 24V DC · Power per Meter: 15 W · Lifetime L70: >= 36.000 h · WxH in mm: 16 x 17 · Temperature range: -40 to +50°C · Processing temperature: +10 to +50°C · Maximum length per connection: 10 meter · Bending radius horizontal: 150 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094665832
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per LED	6.11 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Platin Ultra SVQ - 2700K LD
S?-?? Flex.LEDStrip, 24V, UWW
Article nr.: S76583

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 50
LED per meter	108
Dimension of segments	55.56 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Platin Ultra SVQ - 2700K LD
S?-?? Flex.LEDStrip, 24V, UWW
Article nr.: S76583

TECHNICAL DRAWING

