




VARDAflex Platin Piko Ultra TVQ-RGBW-27 LD ST-?? Flex.LEDStrip, 24V, RGBW-2700K

Article nr.: S76666

Flexible LED-Strip sealed in UV, chlorine, salt water · and solvent-resistant white silicone · for indoor- and outdoor use, IP66 · · cuttable every 100 mm or 14 LED · number of LED per metre: 140 · LED pitch: 7.14 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 366 lm · power per meter: 9 W · lifespan L70B50: >= 36,000 h · WxH in mm: 10 x 10 · · temperature range: -40 bis +60°C · processing temperature: +10 bis +60°C · maximum length per connection: 5 metres · bending radius vertically: 50 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094666662
Housing colour	Weiss
Width	10.00 mm
Height	10.00 mm
LED colour	RGBW 2700K
Lamp	including LED
IP rating	66
Voltage	24 V
Material	Kunststoff






VARDaflex Platin Piko Ultra TVQ-RGBW-27 LD ST-?? Flex.LEDStrip, 24V, RGBW-2700K

Article nr.: S76666

TECHNICAL DATA

Temperature range	-40 - 55
LED per meter	140
Dimension of segments	100.00 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





**VARDAflex Platin Piko Ultra TVQ-RGBW-
27 LD ST-?? Flex.LEDStrip, 24V, RGBW-
2700K**

Article nr.: S76666

TECHNICAL DRAWING

