




VARDAflex Platin Piko Ultra TVQ - 2800K LD S?-?? Flex.LEDStrip, 24V, QH3

Article nr.: S76667

Flexible LED-Strip sealed in UV, chlorine, salt water · and solvent-resistant white silicone · for indoor- and outdoor use, IP66 · · cuttable every 83.33 mm or 12 LED · Number of LED per metre: 144 · LED Pitch: 6.94 mm · Beam Angle: 120° · CRI: > 80 · Luminous flux per meter: 440 lm · Power per meter: 9 W · Lifespan L70: >= 36.000 h · WxH in mm: 10 x 10 · · Temperature range: -40 bis +60°C · Processing temperature: +10 bis +60°C · Maximum length per connection: 15 metres · Bending radius vertically: 50 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094666679
Housing colour	Weiss
Width	10.00 mm
Height	10.00 mm
Lightoutput per LED	3.06 lm
Lamp	including LED
IP rating	66
Voltage	24 V
Material	Kunststoff






**VARDAflex Platin Piko Ultra TVQ -
2800K LD S?-?? Flex.LEDStrip, 24V, QH3**
Article nr.: S76667

TECHNICAL DATA

Temperature range	-40 - 60
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





**VARDAflex Platin Piko Ultra TVQ -
2800K LD S?-?? Flex.LEDStrip, 24V, QH3**
Article nr.: S76667

TECHNICAL DRAWING

