



VARDAflex Platin SVQ Single - 3000K LD **S?-?? Flex.LEDStrip, 24V, WW** Article nr.: S76675

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solvent- and heat-resistant special silicone · for indoor- and outdoor use, IP67/68 · cuttable every 18.52 mm / 2 LEDs · amount of LEDs per meter: 108 · LED pitch: 9.26 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 773 lm · voltage: 24V DC · power per meter: 15 W · lifespan L70B50: >= 36,000 h · WxH in mm: 16 x 17 · temperature range: -40 to +55°C · installation temperature: +10 to +55°C · maximum length per connection: 15 meter · Bending radius horizontal: 150 mm · This product contains a light source of energy efficiency class E.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094666754
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per LED	7.16 lm
Lamp	including LED
IP rating	68
Voltage	24 V



VARDAflex Platin SVQ Single - 3000K LD
S?-?? Flex.LEDStrip, 24V, WW
Article nr.: S76675

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 55
LED per meter	108
Dimension of segments	18.52 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	



VARDAflex Platin SVQ Single - 3000K LD
S?-?? Flex.LEDStrip, 24V, WW
Article nr.: S76675

TECHNICAL DRAWING

