



VARDAflex Platin Piko Ultra SVQ - 2700K LD S?-?? Flex.LEDStrip, 24V, UWW CRI90

Article nr.: S76753

Flexible LED-Strip sealed in UV, chlorine, salt water · and solvent-resistant white silicone · for indoor- and outdoor use, IP66 · · cuttable every 83.33 mm or 12 LED · number of LED per metre: 144 · LED Pitch: 6.94 mm · beam angle: 120° · CRI: > 90, R9: > 90 · luminous flux per meter: 425 lm · power per meter: 9 W · lifespan L70B50: >= 36,000 h · WxH in mm: 10 x 10 · · Temperature range: -40 bis +60°C · Processing temperature: +10 bis +60°C · Maximum length per connection: 7.5 metres · Bending radius horizontal: 50 mm · This product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	metre
BAR code	4012094767536
Housing colour	Weiss
Width	10.00 mm
Height	10.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per LED	2.95 lm
Lamp	including LED
IP rating	66
Voltage	24 V






**VARDAflex Platin Piko Ultra SVQ -
2700K LD S?-?? Flex.LEDStrip, 24V,
UWW CRI90**

Article nr.: S76753

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 60
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 90
Lifetime L70B50	36.000 h
Suitable light source	





**VARDAflex Platin Piko Ultra SVQ -
2700K LD S?-?? Flex.LEDStrip, 24V,
UWW CRI90**

Article nr.: S76753

TECHNICAL DRAWING

