




VARDAflex Platin Piko Ultra SVQ - 3000K LD S?-?? Flex.LEDStrip, 24V, WW CRI90

Article nr.: S76755

Flexible LED-Strip sealed in UV, chlorine, salt water · and solvent-resistant white silicone · for indoor- and outdoor use, IP66 · · cuttable every 83.33 mm or 12 LED · number of LED per metre: 144 · LED Pitch: 6.94 mm · beam angle: 120° · CRI: > 90, R9: > 90 · luminous flux per meter: 440 lm · power per meter: 9 W · lifespan L70B50: >= 36,000 h · WxH in mm: 10 x 10 · · Temperature range: -40 bis +60°C · Processing temperature: +10 bis +60°C · Maximum length per connection: 7.5 metres · Bending radius horizontal: 50 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094767550
Housing colour	Weiss
Width	10.00 mm
Height	10.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per LED	3.05 lm
Lamp	including LED
IP rating	66
Voltage	24 V






VARDaflex Platin Piko Ultra SVQ - 3000K LD S?-?? Flex.LEDStrip, 24V, WW CRI90

Article nr.: S76755

TECHNICAL DATA

Material	Kunststoff
Temperature range	-40 - 60
LED per meter	144
Dimension of segments	83.33 mm
CRI	≥ 90
Lifetime L70B50	36.000 h
Suitable light source	





**VARDAflex Platin Piko Ultra SVQ -
3000K LD S?-?? Flex.LEDStrip, 24V, WW
CRI90**

Article nr.: S76755

TECHNICAL DRAWING

