



VARDAflex Neon - Amber LD S?-??


Flex.LEDStrip, 24V, Amber

Article nr.: S86031

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solventresistant white PVC · for indoor- and outdoor use, IP67/68 · · Cuttable every 166.67 mm / 10 LEDs · Amount of LEDs per meter: 60 · LED pitch: 16.67 mm · Beam angle: 160° · CRI: - · Luminous flux per meter: 100 lm · Voltage: 24V DC · Power per Meter: 7,2 W · Lifetime L70: >= 36.000 h · Energy efficiency class: B · WxH in mm: 11.5 x 21 · · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 10 meter · Bending radius: 60 mm · anti-wicking ferrule diameter = 12 mm: the anti-wicking ferrule is located at · 115 mm from the connector on the cable. · the anti-wicking ferrule is not included in the rutecl Lightdesign version.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094760315
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	Gelb/Amber
Lightoutput per LED	1.67 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Neon - Amber LD S?-??
Flex.LEDStrip, 24V, Amber
Article nr.: S86031

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	166.67 mm
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Neon - Amber LD S?-??
Flex.LEDStrip, 24V, Amber
Article nr.: S86031

TECHNICAL DRAWING

