



VARDAflex Neon - Blau LD S?-??


Flex.LEDStrip, 24V, Blau

Article nr.: S86032

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solventresistant white PVC · for indoor- and outdoor use, IP67/68 · · Cuttable every 100 mm / 6 LEDs · Amount of LEDs per meter: 60 · LED pitch: 16.67 mm · Beam angle: 160° · CRI: >70 · Luminous flux per meter: 44 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · Energy efficiency class: B · WxH in mm: 11.5 x 21 · · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 10 meter · Bending radius: 60 mm · anti-wicking ferrule diameter = 12 mm: the anti-wicking ferrule is located at · 115 mm from the connector on the cable. · the anti-wicking ferrule is not included in the rutecl Lightdesign version.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094760322
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	Blau
Lightoutput per LED	0.73 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Neon - Blau LD S?-??

Flex.LEDStrip, 24V, Blau

Article nr.: S86032

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Neon - Blau LD S?-??
Flex.LEDStrip, 24V, Blau
Article nr.: S86032

TECHNICAL DRAWING

