



VARDAflex Neon - 2700K CRI80 S?-??

Flex.LEDStrip, 24V, UWW

Article nr.: S86037

Flexible LED Stripe sealed in UV-, chlorine-, · salt water-, solventresistant white PVC · for indoor- and outdoor use, IP67/68 · · Cuttable every 100 mm / 6 LEDs · Amount of LEDs per meter: 60 · LED pitch: 16.67 mm · Beam angle: 160° · CRI: >80 · Luminous flux per meter: 350 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · WxH in mm: 11.5 x 21 · · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 10 meter · Bending radius: 120 mm · anti-wicking ferrule diameter = 12 mm: the anti-wicking ferrule is located at · 115 mm from the connector on the cable. · the anti-wicking ferrule is not included in the rutecl Lightdesign version.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094760377
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per LED	5.83 lm
Lamp	including LED
IP rating	68
Voltage	24 V






VARDAflex Neon - 2700K CRI80 S?-??

Flex.LEDStrip, 24V, UWW

Article nr.: S86037

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
CRI	≥ 80
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Neon - 2700K CRI80 S?-??
Flex.LEDStrip, 24V, UWW
Article nr.: S86037

TECHNICAL DRAWING

