



## **VARDAflex Neon TVQ RGB LD S?-??**


### **Flex.LEDStrip, 24V, RGB**

Article nr.: S86071

Flexible LED Stripe sealed in UV-, chlorine-, salt water- and solvent resistant white PVC · for indoor- and outdoor use, IP68 · Cuttable every 83.33 mm / 7 LEDs · Amount of LEDs per metre: 84 · LED pitch: 11.91 mm · Beam angle: 160° · CRI: - · Light flux per meter: 450 lm · Voltage: 24 V DC · Power per metre: 12 W · Lifetime L70: >= 36.000 h · WxH in mm: 16 x 17 · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 7 meters · bending radius: 150 mm

#### **TECHNICAL DATA**

|                     |               |
|---------------------|---------------|
| Unit Code           | metre         |
| BAR code            | 4012094760711 |
| Housing colour      | Weiss         |
| Width               | 16.00 mm      |
| Height              | 17.00 mm      |
| LED colour          | RGB           |
| Lightoutput per LED | 5.36 lm       |
| Lamp                | including LED |
| IP rating           | 68            |
| Voltage             | 24 V          |






**VARDAflex Neon TVQ RGB LD S?-??**  
**Flex.LEDStrip, 24V, RGB**  
Article nr.: S86071

## TECHNICAL DATA

|                       |            |
|-----------------------|------------|
| Material              | Kunststoff |
| Temperature range     | -20 - 45   |
| LED per meter         | 84         |
| Dimension of segments | 83.33 mm   |
| Lifetime L70B50       | 36.000 h   |
| Suitable light source |            |





**VARDAflex Neon TVQ RGB LD S?-??**  
**Flex.LEDStrip, 24V, RGB**  
Article nr.: S86071

## TECHNICAL DRAWING

