



VARDAflex Neon RGBW-3000K LD S? Flex.LEDStrip, 24V, RGBW

Article nr.: S86135

flexible LED Stripe sealed in UV-, chlorine-, salt water- and solvent resistant white PVC · for indoor- and outdoor use, IP68 · cuttable every 100 mm / 6 LEDs · amount of LEDs per meter: 60 · LED pitch: 16.67mm · beam angle: 160° · CRI: >70 · luminous flux per meter: 450 lm · power per meter: 15 W · lifetime L70: >= 36.000 h · WxH in mm: 11.5 x 21 · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending radius: 60 mm · attention: do not run all colors at same time on · maximum load (max. 80%) · anti-wicking ferrule diameter = 15 mm: the anti-wicking ferrule is located at 115 mm from the connector on the cable. · the anti-wicking ferrule is not included in the rutecl Lightdesign version.

TECHNICAL DATA

Unit Code	metre
BAR code	4012094761350
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	RGBW 3000K
Lightoutput per LED	7.50 lm
Lamp	including LED
IP rating	68
Current mA	625 mA






VARDAflex Neon RGBW-3000K LD S?-?? Flex.LEDStrip, 24V, RGBW

Article nr.: S86135

TECHNICAL DATA

Voltage	24 V
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
CRI	≥ 70
Lifetime L70B50	36.000 h
Suitable light source	





VARDAflex Neon RGBW-3000K LD S?-??
Flex.LEDStrip, 24V, RGBW
Article nr.: S86135

TECHNICAL DRAWING

