rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Neon RGBW-2700K LD S?-??
Flex.LEDStrip, 24V, RGBW

Article nr.: S86136

flexible LED Stripe sealed in UV-, chlorine-, · salt water- and solvent resistant white PVC · for indoor- and outdoor use, IP68 · · cuttable every 100 mm / 6 LEDs · amount of LEDs per meter: 60 · LED pitch: 16.67 mm · beam angle: 160° · CRI: >70 · luminous flux per meter: 450 lm · power per meter: 15 W · lifetime L70: >= 36.000h · WxH in mm: 11.5 x 21 · · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending radius: 60 mm · attention: do not run all colors at same time on · maximum load (max. 80%)

TECHNICAL DATA

Unit Code	metre
BAR code	4012094761367
Housing colour	Weiss
Width	11.50 mm
Height	21.00 mm
LED colour	RGBW 2700K
Lightoutput per LED	7.50 lm
Lamp	including LED
IP rating	68
Voltage	24 V

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Neon RGBW-2700K LD S?-??
Flex.LEDStrip, 24V, RGBW

Article nr.: S86136

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
CRI	≥ 70
Lifetime L70B50	36.000 h
Suitable light source	

rutec LIGHTDESIGN GmbH | Carl-Zeiss-Str. 13 | 28857 Syke
TEL +49 4242 / 84034 - 0 | E-MAIL INFO@RUTECLIGHTDESIGN.DE | WWW.RUTECLIGHTDESIGN.DE



VARDAflex Neon RGBW-2700K LD S?-??
Flex.LEDStrip, 24V, RGBW

Article nr.: S86136

TECHNICAL DRAWING





